



# DC FAN FUNCTION TEST RECORD

## FOR LIFE EXPERIMENT

Available for these models with lower speed and same physical structure. All model may be followed by Rx or Fxx series suffixes. This test report applies to AFB92x92x15 mm series as the right table					AFC0912DB-F00				
Required Test Time (hrs)	Date for Test Beginning	Date for Test Termination	Sample Size (pcs):	Failure (pcs):	Current Total Test Time (hrs)				
6,956	2004/5/31 6:30 PM	2005/5/9 10:33 PM	56	0	<b>6956.0</b>				
Representative Test P/N :AFB0912HBB-F00			Current Test Status		<input type="checkbox"/> In process	<input type="checkbox"/> In process (exceed requested)	<input checked="" type="checkbox"/> Termination		
Equipment: 1.Oven: E24-F0052					On/Off Cycles: Every 500 hours				
Test Data Between Initial Test and Final Test									
Sample No.	Initial Test	Final Test	Deviation (%)	Initial Test	Final Test	Deviation (%)	Initial Test	Final Test	Deviation (%)
	Current Spec. ( A )	Current Spec. ( A )		Speed Spec. ( RPM )	Speed Spec. ( RPM )		Noise Spec. ( dB A )	Noise Spec. ( dB A )	
36	0.28	0.28	0.0	3342	3353	0.3	42.1	41.3	-1.9
37	0.29	0.29	0.0	3411	3389	-0.6	41.8	41.5	-0.7
38	0.29	0.29	0.0	3340	3478	4.1	41.6	41.2	-1.0
39	0.29	0.28	-3.4	3245	3425	5.5	41.1	41.0	-0.2
40	0.29	0.30	3.4	3403	3398	-0.1	41.4	41.7	0.7
41	0.30	0.30	0.0	3360	3388	0.8	41.6	41.5	-0.2
42	0.28	0.29	3.6	3357	3450	2.8	41.3	41.6	0.7
43	0.29	0.30	3.4	3364	3433	2.1	41.2	42.1	2.2
44	0.29	0.30	3.4	3389	3393	0.1	41.7	42.0	0.7
45	0.28	0.29	3.6	3354	3449	2.8	41.4	41.8	1.0
46	0.28	0.29	3.6	3430	3420	-0.3	41.5	41.5	0.0
47	0.29	0.29	0.0	3399	3344	-1.6	41.6	41.3	-0.7
48	0.30	0.29	-3.3	3397	3377	-0.6	41.7	41.0	-1.7
49	0.29	0.29	0.0	3349	3392	1.3	41.4	41.7	0.7
50	0.30	0.29	-3.3	3423	3420	-0.1	41.3	41.2	-0.2
51	0.28	0.30	7.1	3319	3357	1.1	41.5	41.8	0.7
52	0.27	0.28	3.7	3217	3489	8.5	41.2	41.6	1.0
53	0.28	0.28	0.0	3377	3486	3.2	41.1	41.4	0.7
54	0.28	0.28	0.0	3341	3411	2.1	41.4	41.5	0.2
55	0.29	0.28	-3.4	3357	3358	0.0	41.6	41.3	-0.7
56	0.30	0.31	3.3	3361	3367	0.2	41.5	41.5	0.0
X-Bar	0.293	0.295	-	3377.1	3405.3	-	41.57	41.57	-
σ	0.010	0.010	-	54.635	45.936	-	0.336	0.312	-
QE File No.		Time-out for function test or others (hrs)		Issued Date		Reported By		Approved By	
DG04FNL158		1280.50		2005/5/9 11:00 PM		Guie.Lin		Gx.Xu	



# DC FAN FUNCTION TEST RECORD

## FOR LIFE EXPERIMENT

Available for these models with lower speed and same physical structure.  
All model may be followed by Rx or Fx series suffixes. This test report  
applies to AFB92x92x15 mm series as the right table

AFC0912DB-F00				

Required Test Time (hrs)	Date for Test Beginning	Date for Test Termination	Sample Size (pes):	Failure (pes):	Current Total Test Time (hrs)
6,956	2004/5/31 6:30 PM	2005/5/9 10:33 PM	56	0	<b>6956.0</b>
Representative Test P/N :AFB0912HBB-F00			Current Test Status	<input type="checkbox"/> In process	<input type="checkbox"/> In process (exceed requested) <input checked="" type="checkbox"/> Termination
Equipment: 1.Oven: E24-F0052			On/Off Cycles: Every 500 hours		

### Test Data Between Initial Test and Final Test

Sample No.	Initial Test	Final Test	Deviation (%)	Initial Test	Final Test	Deviation (%)	Initial Test	Final Test	Deviation (%)
	Current Spec. (A)	Current Spec. (A)		Speed Spec. (RPM)	Speed Spec. (RPM)		Noise Spec. (dB A)	Noise Spec. (dB A)	
1	0.32	0.32	0.0	3488	3482	-0.2	41.9	41.7	-0.5
2	0.29	0.30	3.4	3430	3401	-0.8	42.1	41.7	-1.0
3	0.28	0.28	0.0	3389	3399	0.3	41.2	41.3	0.2
4	0.30	0.30	0.0	3405	3449	1.3	41.3	41.9	1.5
5	0.31	0.31	0.0	3354	3476	3.6	41.5	41.2	-0.7
6	0.30	0.30	0.0	3423	3444	0.6	41.6	41.0	-1.4
7	0.30	0.31	3.3	3413	3360	-1.6	41.7	41.2	-1.2
8	0.29	0.29	0.0	3393	3380	-0.4	42.3	41.7	-1.4
9	0.30	0.30	0.0	3397	3369	-0.8	42.4	41.5	-2.1
10	0.29	0.30	3.4	3412	3386	-0.8	42.5	41.6	-2.1
11	0.31	0.30	-3.2	3415	3487	2.1	41.9	41.2	-1.7
12	0.30	0.31	3.3	3419	3370	-1.4	41.3	41.5	0.5
13	0.29	0.30	3.4	3431	3371	-1.7	41.2	41.7	1.2
14	0.31	0.31	0.0	3421	3398	-0.7	41.4	41.5	0.2
15	0.31	0.32	3.2	3421	3351	-2.0	41.7	41.2	-1.2
16	0.30	0.30	0.0	3421	3424	0.1	42.0	42.0	0.0
17	0.29	0.30	3.4	3332	3448	3.5	41.7	41.5	-0.5
18	0.28	0.28	0.0	3382	3336	-1.4	41.4	41.2	-0.5
19	0.30	0.30	0.0	3375	3335	-1.2	41.1	41.9	1.9
20	0.29	0.28	-3.4	3247	3351	3.2	42.0	42.2	0.5
21	0.28	0.29	3.6	3338	3382	1.3	41.4	41.8	1.0
22	0.29	0.29	0.0	3247	3345	3.0	41.5	41.5	0.0
23	0.30	0.30	0.0	3380	3379	0.0	41.9	41.7	-0.5
24	0.30	0.30	0.0	3405	3345	-1.8	41.3	41.3	0.0
25	0.29	0.28	-3.4	3440	3443	0.1	41.4	41.6	0.5
26	0.29	0.30	3.4	3419	3446	0.8	41.7	41.9	0.5
27	0.29	0.29	0.0	3327	3337	0.3	41.2	42.1	2.2
28	0.31	0.31	0.0	3400	3470	2.1	42.1	41.7	-1.0
29	0.29	0.29	0.0	3396	3433	1.1	41.5	41.3	-0.5
30	0.30	0.30	0.0	3336	3424	2.6	41.6	41.5	-0.2
31	0.30	0.30	0.0	3470	3437	-1.0	41.7	41.9	0.5
32	0.28	0.28	0.0	3292	3347	1.7	41.4	42.1	1.7
33	0.30	0.30	0.0	3426	3479	1.5	41.5	42.3	1.9
34	0.30	0.29	-3.3	3337	3424	2.6	41.0	41.7	1.7
35	0.30	0.30	0.0	3402	3409	0.2	41.3	41.5	0.5

QE File No.	Time-out for function test or others (hours)	Issued Date	Reported By	Approved By
DG04FNL158	1280.50	2005/5/9 11:00 PM	Guie.Lin	Gx.Xu



# DC FAN LIFE EXPERIMENT REPORT

Available for these models with lower speed and same physical structure. All model may be followed by Rxx or Fxx series suffixes. This test report applies to <b>AFB92x92x15 mm</b> series as the right table	AFC0912DB-F00				

**Representative Test P/N :AFB0912HKB-F00**

**Equipment:** 1.Oven: E24-F0052      **On/Off Cycles:** Every 500 hours

◎ L<sub>10</sub> Expectancy: 70,000 hours minimum @ fan rated voltage and the temperature of 40°C

According to the equation for **Weibull distribution**,  $\text{MTTF} \doteq 7 \times \text{L10} = 490,000 \text{ hours}$

And we rely on a zero failure Weibull test strategy and accelerated testing technique, to determine

the total test time ( $t$ ) for verifying the above life estimation by the equations,

$$t = 1.036 \times MTTF \times [(B_{r;c}) / n]^{0.91} / A_F, \text{ and } A_F = 2^{(Ts-Tu)/10}$$

where,  $(B_{r;c})$  is Poisson distribution factor with the failure number of  $r$  equal to 0 and

the decimal confidence level of  $c$  equal to 0.90(90%).

Stress/Elevated Temperature Ts (°C) ( Actual Test Temperature )	Unstress Temperature Tu (°C)	Acceleration Factor A <sub>F</sub>	Quantity of Test Devices n (pcs)	Poisson Distribution Factor B <sub>r;c</sub>	Required test time with zero failure t (hours)	Actual test time with zero failure t (hours)	Verified MTTF 40 °C (hours)	Verified L <sub>10</sub> 40 °C (hours)
60	40	4.00	56	2.303	6,956	6,956.0	490,031	70,004

## Test Progress:

Date for Test Beginning	Date for Test Termination (at least)	Current Test Status			Current Total Test Time (hours)
2004/5/31 6:30 PM	2005/5/9 10:33 PM	<input type="checkbox"/> In process	<input type="checkbox"/> In process (exceed requested)	<input checked="" type="checkbox"/> Termination	<b>6956.0</b>

Herewith , we could assume as right on the basis of above test result. Besides, if the actual test time exceed the required, it comes out that those fans'  $L_{10}$  expectancy and MTTF are greater than the warrant. ( **MTTF** : means Mean Time To Failures, it should be used in a non-repairable system setting. Now we show the MTTF in our life report, that's because we will not repair the failed fans during life experiment. **MTBF**: means Mean Time Between failures, it should be used in a repairable system setting. )

Temperature for MTTF Estimation (°C)	Acceleration Factor A <sub>F</sub>	Estimated MTTF (hours)	Estimated L <sub>10</sub> (hours)
25	11.31	1,386,017	198,002
30	8.00	980,062	140,009
40	4.00	490,031	70,004
50	2.00	245,015	35,002
60	1.00	122,508	17,501
<b>Test Result</b>		<input checked="" type="checkbox"/>	<b>Accept</b>
		<input type="checkbox"/>	<b>Reject</b>

QE File No.	Time-out for function test or others (hours)	Issued Date	Reported By	Approved By
DG04FNL158	1280.50	2005/5/9 11:00 PM	Guie.Lin	Gx.Xu

Note: The test sample equivalent to STD , Part umber: AFB0912HKB-F00.